

Appliance Tee

Quickly connects an existing pipe turn, with isolation on the branch for an appliance supply feed

Overview

Speedfit push-fit fitting allows isolation of appliances such as washing machines or dishwashers for maintenance or installation. Simply push the fitting fully onto the pipe and thread the appliance hose onto the valve. To demount the push-fit end, pull the collet towards the body of the fitting and pull the pipe to release.

The fitting is quicker and easier to install in confined spaces than traditional methods as it eliminates the need for hot works or tools.

Designed, manufactured and assembled in the UK.

Features & Benefits

- Quickly connects an appliance to the water supply
- Integrated 1/4 turn shut off valve
- Install and demount in seconds without tools
- Safe flame-free installation, with no hot works, glue or flux
- Grip & Seal collet with stainless steel teeth and main O-Ring seal
- Suitable for use with JG Speedfit PEX and polybutylene barrier pipe (inserts required) and copper pipe
- Suitable for hot and cold water (not suitable for central heating systems)



Product code	Description	Size	Bag QTY
15APT2	Appliance Tee	15mm x 3/4" BSP	5

Appliance Tee

Working parameters & specifications

Application	Usual working temperature °C	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	20	12
Intermittent Hot Water Use	65	65	6

Materials	
Body	Polyacetal (Unfilled) White
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Polyacetal (Unfilled) White, Stainless Steel
Shut-Off Plugs	Ethylene Polypropylene Diene Monomer (EPDM)
Actuating Pin	Polyacetal (Unfilled) White
Control Knob	Polyacetal (Unfilled) White
Half Cartridge	Polyacetal (Unfilled) Black, Stainless Steel
Support Washer	Polyacetal (Unfilled) Light Blue
Caps	Polyacetal (Unfilled) White

Dimensions – All measurements in mm unless otherwise stated

