

Wing Back Elbow

**Quick and secure installation of MDPE to BSP
For Fast and secure installation
of Bib style taps**

Overview

Speedfit plastic push-fit fitting for the quick and secure installation of Bib style taps. Simply push the fitting fully onto the pipe and twist the plastic nut clockwise to lock in place.

To demount the connection, unlock the nut by hand and push the collet towards the body of the fitting and pull the pipe to release.

The fitting is quicker and easier to install in confined spaces than traditional methods as it eliminates the need for hot works or tools.

Designed, manufactured and assembled in the UK.

Features & Benefits

- Instant push-fit connection
- Install and demount in seconds without tools
- Safe flame-free installation, with no hot works, glue or flux
- Grip & Seal cartridge with stainless steel teeth and main O-Ring seal
- Twist & Lock mechanism secures fitting and adds compression
- Non-toxic, resists corrosion and no scale build-up
- Compatible with MDPE pipes (inserts required)
- Suitable for cold water use only



Product code	Description	Size	Bag QTY
UGPW1514	Wingback Elbow	15mm x 1/2" BSP	1



Back Plate Elbow

Working parameters & specifications

Application	Usual working temperature °C	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	20	12

Materials	
Body	Polypropylene (Glass Filled), Black
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Acetal Copolymer (Unfilled) Black
Collet Teeth	Stainless Steel
Cap	Nylon 66 (Mineral Filled), Black
Thread Ring	Stainless Steel

Dimensions – All measurements in mm unless otherwise stated



Dimensions in mm