

Emergency Shut Off Tap

Slimline 1/4 turn shut off valve for emergency isolation to appliances

Overview

Speedfit push-fit valve allows the user to stop the flow of water to a fixture or zone in the event of an emergency or repair work. Simply push the valve fully onto the pipe and turn the knob on top of the fitting to allow or restrict the flow of water. To demount the connection, push the collet towards the body of the fitting and pull the pipe to release.

The fitting is quicker and easier to install in confined spaces than traditional methods as it eliminates the need for hot works or tools.

Designed, manufactured and assembled in the UK.

Features & Benefits

- Simple hand turn of the knob instantly isolates water
- Install and demount in seconds without tools
- Safe flame-free installation, with no hot works, glue or flux
- Grip & Seal collet with stainless steel teeth and main O-Ring seal
- Suitable for use with JG Speedfit PEX and polybutylene barrier pipe (inserts required) and copper pipe
- Suitable for hot and cold water (no suitable for central heating systems)



Product code	Description	Size	Bag QTY
15ESOT	Emergency Shut Off Tap	15mm	5

Emergency Shut Off Tap

Working parameters & specifications

Application	Usual working temperature °C	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	20	12
Hot Water (including unvented cylinders)	65	95	6

Materials

Body	Acetal Copolymer (Unfilled), White
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Acetal Copolymer (Unfilled), White and Stainless Steel
Control Knob	Acetal Copolymer (Unfilled), White
Actuating Pin	Acetal Copolymer (Unfilled), Natural
Retaining Clip	Acetal Copolymer (Unfilled), Black
Support Washer	Acetal Copolymer (Unfilled), Light Blue

Dimensions – All measurements in mm unless otherwise stated

