

Equal Tee

Push-fit fitting that safely and securely connects 3 pipes of equal connection size

Overview

The JG Speedfit Equal Tee is a plastic push-fit fitting for the connection of three equal sized plastic or copper pipes. Simply push the fitting fully onto the pipe and twist the plastic nut clockwise to lock in place. To demount the connection, unlock the nut by hand and push the collet towards the body of the fitting and pull the pipe to release.

The fitting is up to 40% faster to install than traditional methods and is easier to use in confined spaces by removing the need for hot works and tools.

Designed, manufactured and assembled in the UK.

Features & Benefits

- Instant push-fit connection
- Install and demount in seconds without tools
- Safe flame-free installation, with no hot works, glue or flux
- Grip & Seal collet with stainless steel teeth and main O-Ring seal
- Twist & Lock mechanism secures fitting and adds compression
- Non-toxic, resists corrosion and no scale build-up
- Suitable for use with JG Speedfit PEX and polybutylene barrier pipe (inserts required) and copper pipe
- Suitable for hot and cold water and central heating systems



Product code	Description	Size	Bag QTY
PEM0210W	JG Speedfit Equal Tee	10mm	10
PEM0215W	JG Speedfit Equal Tee	15mm	10
PEM0222W	JG Speedfit Equal Tee	22mm	5
PEM0228W	JG Speedfit Equal Tee	28mm	2



50 year guarantee when used with JG Speedfit Layflat PB and PEX Barrier Pipes

Equal Tee

Working parameters & specifications

Application	Usual working temperature °C	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	20	12
Central Heating	82	105, short term malfunction at 114	3
Hot Water (including unvented cylinders)	65	95	6

Materials

Body	X-Linked Polyethylene, White
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Glass Filled Nylon
Collet Teeth	Stainless Steel 301
Caps	Nylon 66 (40% Mineral Filled), White

Dimensions – All measurements in mm unless otherwise stated

Product code	A	B	C	D
PEM0210W	10mm	56.8*	28.4*	20.2
PEM0215W	15mm	80.7*	40.4*	29.5
PEM0222W	22mm	107.1*	53.6*	36.8
PEM0228W	28mm	122.8	61.4*	42.1

*With Collet(s) in release position

