

Speedfit x Hand Tighten (White PVC) Flexi Hose

Connects a supply to a tap or other fixture or appliance

Overview

Speedfit hand tighten flexi hose for the connection to a male thread appliance, such as a Tap. The white PVC hose material significantly reduces hose 'kinking' and makes the product easier to clean.

On one end the hose features a push-fit connection for a supply pipe. On the other end there is a plastic nut which can be hand tightened on to a tap or male thread. To demount the push-fit end, simply push the collet towards the body of the fitting and pull the pipe to release.

The fitting is quicker and easier to install in confined spaces than traditional methods as it eliminates the need for hot works or tools.

Designed, manufactured and assembled in the UK.

Features & Benefits

- An alternative to hard piping to a tap or fixture
- Flexible design makes installation hassle free
- Safe flame-free installation, with no hot works, glue or flux
- White PVC design stops the pipe kinking and makes cleaning easier
- Grip & Seal collet with stainless steel teeth and main O-Ring seal
- Suitable for use with JG Speedfit PEX and polybutylene barrier pipe (inserts required) and copper pipe
- Suitable for hot and cold water only (6 Bar @ 65 °C)



Product code	Description	Size	Bag QTY
300mm			
PFLX15	Speedfit x Union Nut	15mm x 1/2" BSP	2
PFLX16	Speedfit x Union Nut	15mm x 3/4" BSP	2
PFLX22	Speedfit x Union Nut	22mm x 3/4" BSP	2
500mm			
PFLX18	Speedfit x Union Nut	15mm x 1/2" BSP	2
PFLX19	Speedfit x Union Nut	22mm x 3/4" BSP	2



50 year guarantee when used with JG Speedfit Layflat PB and PEX Barrier Pipes

Speedfit x Hand Tighten Flexi Hose

Working parameters & specifications

Application	Maximum working, temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	12
Hot Water (including unvented cylinders)	65	6

Materials	
BSP Hose Barb	Nickel Plated Brass
BSP Captive Nut	Nylon (Mineral Filled), White
Sealing Washer	Ethylene Polypropylene Diene Monomer (EPDM)
Ferule	Stainless Steel
Reinforced Hose	Multilayer PVC/Polyester Fibre Reinforced & Hytrel
Connector Body	Acetal Copolymer (Unfilled), White
Collet	Acetal Copolymer (Unfilled), White & Stainless Steel
Support Washer	Acetal Copolymer (Unfilled), Natural
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)

Dimensions – All measurements in mm unless otherwise stated

