

JG Speedfit x Speedfit Flexi Hose

Connects a supply to a tap or other fixture or appliance

Overview

Speedfit push-fit flexi hose for the connection of plastic or copper pipe. The flexi hose is ideal for the connection of two pipes where the angle is too steep to bend the pipe to make a connection. Simply push the fitting fully onto the pipe. To demount the connection, push the collet towards the body of the fitting and pull the pipe release.

The fitting is quicker and easier to install in confined spaces than traditional methods as it eliminates the need for hot works or tools.

Designed, manufactured and assembled in the UK.

Features & Benefits

- An alternative to hard piping to a tap or fixture
- Flexible design makes installation hassle free
- Safe flame-free installation, with no hot works, glue or flux
- Braided stainless steel outer layer protects the internal feed from damage
- Grip & Seal collet with stainless steel teeth and main O-Ring seal
- Suitable for use with JG Speedfit PEX and polybutylene barrier pipe (inserts required) and copper pipe
- Suitable for hot and cold water only (6 Bar @ 65 °C)



Product code	Description	Size	Bag QTY
150mm			
FLX33P	Speedfit x Speedfit	15 x 10mm	2
300mm			
FLX17P	Speedfit x Speedfit	15 x 15mm	2
FLX26P	Speedfit x Speedfit	22 x 22mm	2
500mm			
FLX21P	Speedfit x Speedfit	15 x 15mm	2
FLX27P	Speedfit x Speedfit	22 x 22mm	2
1000mm			
FLX47	Speedfit x Speedfit	15 x 15mm	5



50 year guarantee when used with JG Speedfit Layflat PB and PEX Barrier Pipes

JG Speedfit x Speedfit Flexi Hose

Working parameters & specifications

Application	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	12
Hot Water (including unvented cylinders)	65	6

Materials	
Body	Acetal Copolymer (Unfilled) Light Grey
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Acetal Copolymer (Unfilled) Light Grey
Collet Teeth	Stainless Steel
Ferule	Stainless Steel
Flexible Hose	Stainless Steel & EPDM

Dimensions – All measurements in mm unless otherwise stated

