

Straight Adaptor (BSP Thread)

Converts an imperial push-fit connection to an imperial threaded connection

Overview

John Guest straight adaptor (BSP thread) push-fit fitting connects imperial pipe to an imperial BSP type thread connection. Fast and simple to install, John Guest Air and Pneumatics creates an instant connection and airtight seal without the need for tools, hot works or sealing agents. Air piping systems can be set up and installed 50% quicker than traditional methods.

The unique collet locking design firmly and securely holds the pipe in place without deforming the pipe or restricting flow. Fittings are also fully demountable, reducing system downtime during maintenance and making it quick and easy to modify or extend systems.

Designed in tough engineered plastic, fittings are compatible with John Guest nylon, powder coated aluminium or LLDPE tubing, as well as copper, PEXa and other soft metal pipe materials. All John Guest fittings are manufactured and assembled in the UK.



Features & Benefits

- Plastic push-fit adaptor for connecting to imperial BSP threads
- Strong acetal copolymer fitting with nitrile O-Ring
- Airtight connection with superior flow characteristics
- Instant push-fit connection and demountable without tools
- Secure collet cover prevents accidental disconnection
- Suitable for air and pneumatics piping systems up to 10 bar
- Ideal for air, inert gases and vacuum applications
- Food grade fitting suitable for potable liquids
- Compatible with soft metal or plastic pipe/tubing

Product code	Description	Size	Bag QTY
PI010812S	Straight Adaptor (BSP Thread)	1/4" x 1/4"	10
PI011212S	Straight Adaptor (BSP Thread)	3/8" x 1/4"	10
PI011213S	Straight Adaptor (BSP Thread)	3/8" x 3/8"	10
PI011613S	Straight Adaptor (BSP Thread)	1/2" x 3/8"	10




Straight Adaptor (BSP Thread)

Working parameters & specifications

Application	Maximum working pressure, bar
Air	16 Bar

Materials	
Body	Plastic
O-Ring	Nitrile, Black
Collet	Acetal Copolymer (Unfilled)
Collet Teeth	Stainless Steel 301

Dimensions – All measurements in mm unless otherwise stated



Product No.	Size	A Tube O/D	B	C	D	E	F	G
PI010812S	1/4" x 1/4 BSP	0.250 +0.001 / -0.004 [6.35 +0.03 / -0.10]	0.62 [15.7]	0.62 [15.7]	0.31 [8.0]	0.21 [5.3]	0.67 [17.0]	0.72 [18.3]
PI011212S	3/8" x 1/4 BSP	0.375 +0.001 / -0.004 [9.53 +0.03 / -0.10]	0.78 [19.7]	0.93 [23.5]	0.31 [8.0]	0.28 [7.1]	0.79 [20.0]	0.79 [21.8]
PI011213S	3/8" x 3/8 BSP		0.78 [19.7]	0.74 [18.9]	0.37 [9.3]	0.28 [7.0]	0.87 [22.0]	0.95 [24.1]
PI011613S	1/2" x 3/8 BSP	0.500 +0.001 / -0.004 [12.7 +0.03 / -0.10]	0.91 [23.0]	1.04 [26.3]	0.37 [9.3]	0.33 [8.5]	0.94 [24.0]	1.04 [26.4]

Dimensions in Inches & [mm]