

Black End Stop

Safe and securely caps microduct termination points

Overview

The JG Blown Fibre Black End Stop is designed for simple installation and seamless performance under the toughest of conditions. Used to cap termination points of pipework. It's a durable easy to use solution in a slimline fitting. Its black colour offers better UV protection. Featuring a collet with stainless steel teeth, the fitting is designed to provide a secure connection with a simple push-fit action. This technology eliminates the need for any tools, making the installation process efficiently straightforward.

Features and benefits

- Black surface gives extra UV protection
- Hard wearing construction for installation into the toughest of conditions
- Push-fit technology ensures swift tool-free installation
- Collet with stainless steel teeth securely locks microduct in place
- O-Ring Seals enhance connection integrity

Product code	Description	Size
NC2284	Black End Stop	3mm
NC2576	Black End Stop	4mm
NC753	Black End Stop	5mm
NC2761	Black End Stop	6mm
PM4618E	Black End Stop	18mm



Black End Stop

Working pressures & temperatures

Blowing pressure (max)	16 bar
Temperature range	-25°C to 60 °C

Applications

Direct buried fibre optic microducts	✓
--------------------------------------	---

Materials

Body	Acetal Copolymer (Unfilled)
Collets & Cartridges	Polypropylene (Unfilled), Stainless Steel
O-Ring	Nitrile, Black

Dimensions

Working Temperatures and Pressures

Temperature (Air);	-10°C to 40°C
Blowing Pressure (max);	16 bar

